

# 噪音偵測大型顯示器



LdB-4 (4.0 英吋)



LdB-2 (2.3 英吋)

## 規格

- Display** : 4 digits ( 4" or 2.3" )
- Sampling time** : < 3 sec.
- Range** : 35~100 dB
- Frequency Range** : 20Hz~12.5KHz
- Accuracy** : ±0.5 dB
- Operating Temp.** : 0~60°C/ below 80%R.H.
- Storage Temp.** : -10~70°C/ below 70% R.H.
- Power Supply** : AC 115/230V±10%, 50/60Hz  
DC 24±20%
- Dielectric Strength** : AC 1500V/1min ( Input/Power )
- Insulation Resistance** : More than 100MΩ at 500VDC

## Relay (option)

Relay output (option) : AC 230V/DC 24V, 5A

## RS-485 Interface (option)

Address : 1 ~ FF (16 Hex)  
Baudrate : 9600, 19.2K, 38.4K, 57.6K, 115.2K  
Frame : N.8.2, E.8.1, O.8.1, N.8.1  
Protocol : Modbus RTU Mode

## 外型尺寸 (包含單位長度100mm)

- 4 英吋 (10cm) : 4 位數, 長 460mm×高 150mm×深 60mm
- 2.3 英吋 (5.8cm) : 長 280mm×高 100mm×深 60mm

## 訂購型號

Model —  —  —

### LED 尺寸

- 2 : 2.3 英吋
- 4 : 4.0 英吋
- 7 : 7.0 英吋



### 輸出

- 1 : Relay × 2 組
- 2 : RS-485
- 3 : Relay × 2 + RS-485
- N : 無




### 工作電源

- 1 : AC 100~240V, 50/60Hz
- 2 : DC 24V

## 腳架尺寸圖 (mm)



側視圖 (4英吋)



側視圖 (2.3英吋)

